



# LINERS TO MEET THE DEMAND FOR EVERY APPLICATION

HammerHead Trenchless carries seven types of liners for CIPP applications to best meet customer needs, unique projects and curing methods. Our liners are constructed of the highest quality material for reliable and consistent installation. Our liner and resin systems are compliant with industry installation standards including ASTM F1216 – *Standard practice for rehabilitation of existing pipelines and conduits by the inversion and curing of resin-impregnated tube*, Uniform Plumbing Code (UPC), International Plumbing Code (IPC), NSF International (NSF14), IAPMO, and ICC-ES.

## HELIAM® SCRIM LINER

Scrim reinforced liner that minimizes longitudinal stretch and assures accurate inversion lengths. This liner can be used for all curing methods. Used in applications 3 to 6 inches in diameter with both straight shot applications and single bends of up to 45°. 5¾" HELIAM Scrim available for 6" undersized cast-iron and clay pipe.

## HELIAM® TRANSITIONAL SCRIM LINER

Scrim reinforced liner is designed to seamlessly combine two diameter sizes of various lengths sewn together to create a liner that is capable of transitioning from 4" to 6". The scrim reinforced liner minimizes longitudinal stretch and assures accurate inversion lengths allowing it to navigate 4" to 6" diameter transitions smoothly. This liner can be used for all curing methods.

## HH FLEX LED LINER

Proprietary synthetic polyester fiber liner with polyurethane coating designed specifically for use with the BlueLight curing system. Used in applications from 3 to 6 inches in diameter to minimize wrinkling and installs through single or multiple bends up to 90° and/or where the host pipe configuration includes single diameter transitions (3 – 4", 4 – 6" and 6 – 8").

## HH LED LINER

Proprietary synthetic polyester fiber liner with polyurethane coating designed specifically for use with the BlueLight curing system. Used in applications 6-10 inches in diameter with single bends up to 45°.

### CURING METHOD



AMBIENT



HOT WATER



BLUELIGHT



AMBIENT



HOT WATER



BLUELIGHT



BLUELIGHT



BLUELIGHT

# IT'S ALL HERE

## CURING METHOD



AMBIENT



HOT WATER



AMBIENT



HOT WATER



AMBIENT



HOT WATER

### HH FLEX LINER

Flexible polyester needle-punched felt liner with polyurethane coating and sewn seam used in applications where the host pipe is 4 to 8-inch diameter with bends of 45° and 90°. Ambient or heat cure using hot water circulation is recommended.

### WOVO/BRAWOLINER

Highly flexible, premium, woven, seamless PET premium liner with polyurethane coating used in applications from 2 to 8-inch diameter to minimize wrinkling and install through single or multiple bends up to 90°. Ambient or heat cure using hot water circulation is recommended.

### WOVO/BRAWOLINER 3D

Premium, woven, seamless PET premium liner with polyurethane coating used in applications to minimize wrinkling and install through single or multiple bends up to 90° and/or where the host pipe configuration includes diameter transitions. Ambient or heat cure using hot water circulation is recommended. Available in 3 to 4, 4 to 6 and 6 to 9-inch transitions.

Liner	Diameter										Bends		Transitions*	Pre-Wetout Liner	Cure Method
	2"	3"	4"	5"	5 <sup>3/4</sup> "	6"	8"	10"	12"	45°	90°				
HELIAM® Scrim Liner		X	X	X	X	X					X			X	Ambient, Hot Water, BlueLight
HELIAM® Transitional Scrim Liner			X			X						X			Ambient, Hot Water, BlueLight
FLEX LED Liner		X	X			X				X	X	X		X	BlueLight
HH LED Liner						X	X	X		X				X	BlueLight
Flex Liner			X	X		X	X			X	X	X			Ambient, Hot Water
Wovo/Brawoliner	X	X	X	X		X	X			X	X				Ambient, Hot Water
Wovo/Brawoliner 3D		X	X	X		X	X			X	X	X			Ambient, Hot Water



\*Single diameter transitions.



REHAB & REPLACEMENT. **REDEFINED**

Get it ALL at:

[hammerheadshop.com](https://hammerheadshop.com)